



Industry Leading Coolants

COOLANT QUOTE

CUSTOMER NAME

DATE

DELIVERY PARTNER

DISCOUNT

ES Compleat OAT	1 Gallon Jug		55 Gallon Drum			275 Gallon Tote		
	Part #	Price	Part #	Price	Price per Gallon	Part #	Price	Price per Gallon
50/50 Premix	CC36077		CC36076			CC36074USR		
Concentrate	CC36073		CC36072			CC36070USR		

ES Compleat NOAT	1 Gallon Jug		55 Gallon Drum			275 Gallon Tote		
	Part #	Price	Part #	Price	Price per Gallon	Part #	Price	Price per Gallon
50/50 Premix	CC36161USJ		CC36161USD			CC36161UST		
Concentrate	CC36166USJ		CC36166USD			CC36166UST		

ES Compleat	1 Gallon Jug		55 Gallon Drum			275 Gallon Tote		
	Part #	Price	Part #	Price	Price per Gallon	Part #	Price	Price per Gallon
50/50 Premix	CC2825		CC2826			CC8983		
Concentrate	CC2820		CC2821			CC8984		

Fleetcool EX	1 Gallon Jug		55 Gallon Drum			275 Gallon Tote		
	Part #	Price	Part #	Price	Price per Gallon	Part #	Price	Price per Gallon
50/50 Premix	CC2746		CC2745			CC2743USR		
Concentrate	CC2742		CC2741			CC2739USR		

Fleetcool	1 Gallon Jug		55 Gallon Drum			275 Gallon Tote		
	Part #	Price	Part #	Price	Price per Gallon	Part #	Price	Price per Gallon
50/50 Premix	CC8974		CC8972			CC8970USR		
Concentrate			CC8967			CC8965USR		

In addition to providing superior freeze and boil-over protection, Fleetguard products protect your engine from the most damaging cooling system problems, including:

- Corrosion
- Solder Bloom
- Acidification
- Liner Pitting & Cavitation
- Scale & Deposits
- Water Pump Leaks



Classification	Conventional	Hybrid	NOAT	OAT
Technology	Good	Better	Better	Best
**Life (miles)	300,000 - 400,000	1,000,000	1,000,000	1,000,000
**Life (hours)	6,000-8,000	20,000	20,000	20,000
Maintenance Requirements	High	Medium	Medium	Low
Product Highlights:	The original fully formulated Heavy Duty coolant. Does <u>not</u> require a pre-charge of SCA.	Life-of-the-engine coolant. Premium product with an extended service interval. Ideal for Cummins HD systems.	Life-of-the-engine coolant. Robust extended life coolant. Ideal for extended life systems (ELC) requiring nitrite.	Life-of-the-engine coolant. 1M mile coolant without the use of extenders or SCAs. Leading technology, environmentally friendly, low maintenance, superior performance, robust product. Phosphate, Nitrite & Silicate free.
*Cummins Recommended Products:	Product: Fleetcool Color: Green	Product: ES Compleat Fleetcool EX Color: Blue Fuchsia	Product: ES Compleat NOAT Color: Red	Product: ES Compleat OAT Color: Red
Performance Standards:	All other coolants: ASTM D3306, ASTM D6210, CES14603, CES14439, OEM Performance Requirements			ES Compleat OAT: ASTM D3306, ASTM D6210, CES14603, CES14439, CES14636, OEM Performance Requirements

Common Cooling System Issues

- Wet sleeve liner pitting
- Additive drop out
- Solder flux contamination
- Premature silicone hose failure
- Water pump cavitation or leaks
- Premature EGR cooler failure
- Premature radiator failure
- Face seal and other deposit build up
- Hot Surface Scaling
- Corrosion

Coolant Performance Specifications

ASTM D3306

- Light duty requirement
- Freeze and boiling point protection
- Basic corrosion protection

ASTM D6210

- Meets heavy duty requirements
- Requires protection against wet sleeve liner pitting and hot surface scaling

Cummins CES Standards

- Ensures compatibility
- Robust Corrosion Protection
- Field Testing