

# VF62

BUILT-IN REFRIGERATOR FOR MOBILE APPLICATION

# VITRIFRIGO

COOL AND BEYOND



VITRIFRIGO COOL AND BEYOND	REFRIGERATOR KITS REFRIGERATOR + INSTALLATION KIT	INSTALLATION KITS REFRIGERATOR SOLD SEPARATELY	COMPRESSOR COVER SOLD SEPARATELY
	VF62	VF62	
FREIGHTLINER P4 CASCADIA <sup>1</sup>	PP607337 (w/ compressor cover)	PP607374 (w/ compressor cover)	PP607330
FREIGHTLINER P4 CASCADIA <sup>2</sup>	PP607240	PP607276	N/A
FREIGHTLINER P4 CASCADIA <sup>3</sup>	PP607241	PP607277	N/A
PETERBILT 379 / 386 / 389 <sup>4</sup>	PP607242	PP607221	N/A

**APPLICATION NOTES:**

- <sup>1</sup> Freightliner P4 / New Cascadia 72" sleeper - Install kit ONLY for P4 / New Cascadia trucks equipped with Data Code: 64E-010 or 719-022. (floor bracket/tray option)
- <sup>2</sup> Freightliner P4 / New Cascadia 72" sleeper - Install kit ONLY for P4 / New Cascadia trucks equipped with Data Code: 64E-012 and 719-998. (storage cabinet option)
- <sup>3</sup> Freightliner P4 / New Cascadia 72" sleeper - Install kit ONLY for P4 / New Cascadia trucks equipped with Data Code: 64E-011 and 719-017. (factory installed fridge option)
- <sup>4</sup> Peterbilt 379 trucks are built with two different cabinets - one fits a VF51 (15" wide) and the other one fits a VF62 (17.5" wide).



**LED LIGHT**

HIGH INTENSITY NEW LED LIGHTING SYSTEM



**AIRLOCK SYSTEM**

STANDARD EQUIPMENT (FLUSH FLANGE / SURFACE FLANGE)



**D-POWER**

DUAL ELECTRONIC BOX (12 VDC - 50/60 HZ)



**RECHARGE**

BD35F COMPRESSOR WITH ACCESSIBLE FREON INLET FOR RECHARGING

- 12 VDC COMPRESSOR DRIVEN COMBO REFRIGERATOR / FREEZER
- 2.2 CU FT COMBINED STORAGE CAPACITY / WEIGHT 42.3 LBS
- RUN TIME IS APPROXIMATELY 35% IN 25°C (77°F) AMBIENT AND INTERNAL TEMPERATURE OF 2.5°C (36.5°F)
- DOOR IS CONSTRUCTED WITH GALVANIZED STEEL FRONT FOR DURABILITY AND INCLUDES REPLACEABLE GLOSS BLACK PANEL
- INSULATION IS HIGH DENSITY, CFC-FREE, POLYURETHANE FOAM
- STORAGE AREA IS WHITE THERMOFORMED PLASTIC FOR EASY CLEANING
- LOW VOLTAGE AND OVER-VOLTAGE PROTECTION
- 40W POWER CONSUMPTION
- MINIMUM ROUGH OPENING 18.375(W) X 21(H) X 21.875(D)
- FORCED AIR, FIN AND TUBE CONDENSER SAVES SPACE AND IMPROVES PERFORMANCE
- DOOR LATCH ASSURES POSITIVE CLOSURE WITH INCORPORATED AIR VENT FOR QUICK RE-ENTRY
- ADJUSTABLE ELECTROMECHANICAL TEMPERATURE CONTROL
- INTERIOR LED LIGHT IS ACTIVATED BY MOTION SENSOR

BROUGHT TO MARKET BY

**PANA-PACIFIC**

(800) 726-2636 CS@PANAPACIFIC.COM